

ChargeMaster 12/15-2



Product code: 43011500

MASTERVOLT
THE POWER TO BE INDEPENDENT

Power you can rely on

- 3-Step+ charging technology for fast and complete charging.
- Safe and complete charging due to standard safety features.
- Memory function prevents overcharging in case of an unstable power supply.
- Clear control panel.
- Easy to install.
- Built-in system functionality (MasterBus) in combination with other Mastervolt products.

Always on course with Mastervolt...

Mastervolt ensures you an electrical system with no weak links and a dependable and silent power supply. Whether for recreational or professional purposes, with Mastervolt you always have power you can rely on... The power to be independent.

ChargeMaster battery chargers

Make the most of your batteries with the ChargeMaster, plugging in and charging anywhere in the world. Mastervolt's ChargeMaster guarantees fast and complete charging of your batteries no matter where you are. The ChargeMaster can charge multiple battery banks simultaneously thanks to its combined functionality. Moreover, all ChargeMasters can be easily connected to a MasterBus network with only one cable and one connection. You also have the option of central, local or remote monitoring, configuration and control of your system. The ChargeMaster is available in various models to guarantee you the ideal battery charger for any situation and demand.

Specifications

General specifications

Nom. output voltage	12 V
Total charge current	15 A
Number of battery outlets	2
Charge current second output	15 A
Battery capacity range	30-150 Ah
Nominal input voltage	230 V (180-265 V), 50/60 Hz
AC connection	cable + plug
Supplies your system without battery	no
Display/read-out	1 LED
Dimensions, hxxwxd	206 x 121 x 50 mm 8.1 x 4.8 x 2.0 inch
Weight	1 kg 2.2 lb
Fastening	screw
Approvals	CE, ABYC A-31

Technical specifications

Charge characteristic	IUoUo, automatic 3-step+ for gel/AGM/wet/Lithium Ion
Charge voltage Bulk	14.25 V
Charge voltage Absorption	14.25 V
Absorption time	6 hours
Charge voltage Float (wet batteries)	13.25 V
Charge voltage Float (gel/AGM batteries)	13.8 V
Temperature compensation	-30 mV/ °C -17 mV/ °F
Voltage compensation	automatic
Power consumption (DC side)	< 1 mA
Full load consumption (230 V AC)	250 W
Current Control function	no
Power factor control	> 0.95
Temperature range (ambient temp.)	-25 °C to 60 °C, derating > 40 °C -13 to 140 °F
Cooling	vario fan
Sound level	< 52 dBA at 1 mtr
Protection degree	IP21
CSI/DC alarm	no
Safety protections	over temperature, over load, short circuit, high/low battery voltage
MasterBus compatible	no