

SPECTRA NEWPORT 400c WATERMAKER

PRODUCT SPECIFICATIONS

400 gal (1514 l) Production / Day Production / Hour 17 gal (64 l)

Power Requirement

12v DC 24A / 24v DC 12A 18 Watts/1 gal 4.8 Watts/1 liter

Weight DC Systems 110 lbs (50 kg)

2.5"x10" pleated polyester 5 micron 2.5"x10" pleated polyester 20 micron Pre Filters

Controls Spectra Connect Controller

Dedicated thruhull, dry and well Installation Requirements

ventilated area not to exceed

110F/37C

40" x 2.5" High rejection spiral wound polyamide Membranes

Pump and Motor Commercial DC motor with carbon

vane pump

99.2% Salt Rejection

Max 110F/37C Min 36F/2C Temperature Range

Baseline Conditions 33,000 PPM feed water at 77F/25C

pH Range 3-11 (typical seawater pH is 8)

Chlorine Tolerance O PPM

Spectra standard warranty Warranty

150 lbs (68 kg) Shipping Weight Shipping Dimensions 47"x23"x18"

120cm x 59cm x 46cm





FACTS

The Newport 400c operates on as little as 15 watts per gallon (4 watts per liter), making it possible to run your system on a small generator, solar, wind, batteries. Multi-speed capacity allows machine operation on high mode for maximum product flow or low mode for maximum efficiency, making it ideal for onboard power management. The system will automatically switch to low mode to extend the prefilter life in challenging feed water. The Spectra Connect allows you to operate and monitor your watermaker from a remote device, and has new added features like the Fill Tank mode, or a customizable Auto Run mode, One-TouchSensor Calibration, and suggested maintenance intervals displayed on the dashboard.

FEATURES

- Completely automated with the Spectra Connect Controller Compact modular design
- Spectra's unique Clark Pump for efficiency and reliability
- High and low speed operation for customizable power management and output volume
- Low power consumption, can be run on batteries, solar, or wind power
- Commercial grade Magdrive pump with run dry protection
- Commercial grade, continuous duty motor
- Manual bypass for diversion valve
- System includes installation kit and product sample valve
- Z±ION Compatible



SPECTRA NEWPORT 400c WATERMAKER



High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm

Katadyn reserves the right to modify products

Katadyn Desalination LLC.

Spectra Watermakers 2220 S McDowell Blvd Ext Petaluma, CA 94954

TEL: 1-415-526-2780 FAX: 1-414-526-2787

E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com